

# Technical Data Sheet

## ECS FLUX-Off

### Art. Nr. 705

#### Product description

FLUX-OFF is a mild, but effective cleaner that easily removes the toughest deposits of flux, soldering oils and other contaminants such as grease, dirt and molding compounds. FLUX-OFF is colorless and leaves no residue. It is used for gentle and intensive cleaning of printed circuit boards, electronic subassemblies and all other electronic components, suitable for degreasing of parts and equipment. It does not attack any material in common use. However, avoid using it on PVC and polystyrene.

#### Application

FLUX-OFF is especially suitable for a gentle, but intensive cleaning of printed circuit boards, electronic sub-assemblies and all other electronic components. Further it is also suitable for the degreasing of installations and appliances. Spray FLUX-OFF thoroughly on residues to be removed. For accurate work, use the attached extension tube. Allow the solvents to act for a time. To protect printed circuit boards after the cleaning process, we recommend the use of PLASTIC and URETHANE. Aerosol can is equipped with 360° valve and can be sprayed overhead.

#### Please Note

Electronical devices to be switched-off during cleaning and plug to be taken out. Cleaning instructions of appliance producer to be taken into account. Further information concerning FLUX-OFF to be found in recent MSDS.



#### Technical Data

Appearance:	Clear, colorless
Odor:	Mild
Density at 25° C:	0,84 g/cm <sup>3</sup>
Material compatibility:	Very good
Evaporation:	Average
Material compatibility:	PE, PP good PC limited PS, PVC incompatible
Surface tension:	22 mN/m

#### Storage / Shelf Life

Shelf life is 5 years if stored correctly.