

Silikon-Spray 400 ml

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 - Product identifier

Trade name/designation Silikon-Spray 400 ml

Chemical name

Product-type Mixture

UFI: 9820-A0QN-J009-17DW

1.2 - Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses - Lubricants, greases, release products

1.3 - Details of the supplier of the safety data sheet

ECS Cleaning Solutions GmbH

Wolfener Str. 32-34

D-12681 Berlin Germany

Telephone : +49 (0)30 / 36 46 40 36

1.4 - Emergency telephone number

- Health and Safety Executive (HSE) (United Kingdom)

Tel. No.: +44 0151 922 9235 United Kingdom

SECTION 2: Hazards identification

2.1 - Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 [CLP]

Skin Irrit. 2	Irritation, Category 2
STOT SE 3 (H336)	STOT-single exposure - Category 3 (H336)
Asp. Tox. 1	Aspiration hazard - Category 1
Aquatic Chronic 2	Hazardous to the aquatic environment - Aquatic Chronic 2
Aerosol 1	Aerosol - Category 1

2.2 - Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Contains: Hydrocarbons, C6, isoalkanes, <5% n-hexane (CAS No.:) | pentane isopentane, 2-methylbutane (CAS No.: 109-66-0)

Signal word : Danger

Hazard pictograms



Hazard statements

H222	Extremely flammable aerosol
H229	Pressurised container: May burst if heated
H315	Causes skin irritation

Silikon-Spray 400 ml

H336	May cause drowsiness or dizziness
H411	Toxic to aquatic life with long lasting effects
Precautionary statements	

P102	Keep out of reach of children.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211	Do not spray on an open flame or other ignition source.
P251	Do not pierce or burn, even after use.
P261	Avoid breathing dust/fume/gas/mist/vapours/spray.
P271	Use only outdoors or in a well-ventilated area.
P280	Wear protective gloves.
P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P410+P412	Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
P501	Dispose of contents/container to an appropriate recycling or disposal facility in accordance with local/regional/national/international regulation.

EUH-phrases : None

2.3 - Other hazards

SECTION 3: Composition / information on ingredients

3.1 - Substances

Not applicable

3.2 - Mixtures

Chemical name	No	%	Class(es)	Specific concentration limit
Hydrocarbons, C6, isoalkanes, <5% n-hexane	CAS No. : Index No. : EC No. : 931-254-9 REACH No. : 01-2119484651-34	20 - 30	Aquatic Chronic 2 - H411 Asp. Tox. 1 - H304 Flam. Liq. 2 - H225 Skin Irrit. 2 - H315 STOT SE 3 (H336) - H336	Not applicable
pentane isopentane, 2-methylbutane	CAS No. : 109-66-0 Index No. : 601-006-00-1 EC No. : 203-692-4	20 - 30	Aquatic Chronic 2 - H411 Asp. Tox. 1 - H304 Flam. Liq. 2 - H225 STOT SE 3 (H336) - H336	Not applicable
butane	CAS No. : 106-97-8 Index No. : 601-004-00-0 EC No. : 203-448-7	20 - 30	Flam. Gas 1 - H220 Press. Gas	Not applicable
propane	CAS No. : 74-98-6 Index No. : 601-003-00-5 EC No. : 200-827-9	1 - 10	Flam. Gas 1 - H220 Press. Gas	Not applicable
isobutane	CAS No. : 75-28-5 Index No. : 601-004-00-0 EC No. : 200-857-2	1 - 10	Flam. Gas 1 - H220 Press. Gas	Not applicable

SECTION 4: First aid measures

4.1 - Description of first aid measures

Following inhalation	- No special measures are necessary. - Provide fresh air.
Following skin contact	- After contact with skin, wash immediately with plenty of water and soap.

Silikon-Spray 400 ml

After eye contact

- In case of skin irritation, consult a physician.
- Rinse immediately carefully and thoroughly with eye-bath or water.
- In case of eye irritation consult an ophthalmologist.

After ingestion

- Rinse mouth thoroughly with water.
- Do NOT induce vomiting.

4.2 - Most important symptoms and effects, both acute and delayed

Symptoms and effects - Following inhalation - No information available.

Symptoms and effects - Following skin contact - Causes skin irritation.

Symptoms and effects - After eye contact - No information available.

Symptoms and effects - After ingestion - No information available.

4.3 - Indication of any immediate medical attention and special treatment needed

- Treat symptomatically.

SECTION 5: Firefighting measures

5.1 - Extinguishing media

Suitable extinguishing media

- ABC-powder
- Carbon dioxide (CO₂)
- Foam
- Extinguishing powder

Unsuitable extinguishing media - Full water jet

5.2 - Special hazards arising from the substance or mixture

Special hazards arising from the substance or mixture - No information available.

5.3 - Advice for firefighters

- Co-ordinate fire-fighting measures to the fire surroundings.

SECTION 6: Accidental release measures

6.1 - Personal precautions, protective equipment and emergency procedures

For non-emergency personnel - Use personal protection equipment.

For emergency responders - No information available.

6.2 - Environmental precautions

- No information available.

6.3 - Methods and material for containment and cleaning up

Methods and material for containment - No information available.

Methods and material for cleaning up - Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

Silikon-Spray 400 ml

- Wash with plenty of water.

Inappropriate techniques

- No information available.

6.4 - Reference to other sections

- Disposal: see section 13

- Personal protection equipment: see section 8

SECTION 7: Handling and storage

7.1 - Precautions for safe handling

Recommendation

- Avoid: Skin contact

- It is recommended to design all work processes always so that the following is excluded: Skin contact

Advices on general occupational hygiene

- No information available.

7.2 - Conditions for safe storage, including any incompatibilities

- No information available.

7.3 - Specific end use(s)

SECTION 8: Exposure controls/personal protection

8.1 - Control parameters

pentane isopentane, 2-methylbutane (109-66-0)

IOELV TWA mg/m3 (UE)	3000 mg/m3
IOELV TWA ppm (UE)	1000 ppm

DNEL / PNEC

Hydrocarbons, C6, isoalkanes, <5% n-hexane

Type	Value	User	Effect
DNEL long-term oral (repeated)	1301 mg/kg bw/day	Consumers	Systemic
DNEL long-term inhalative	5306 mg/m3	Workers	Systemic
DNEL long-term inhalative	1131 mg/m3	Consumers	Systemic
DNEL long-term dermal	1377 mg/kg bw/day	Consumers	Systemic

pentane isopentane, 2-methylbutane (109-66-0)

Type	Value	User	Effect
DNEL long-term oral (repeated)	214 mg/kg bw/day	Consumers	Systemic
DNEL long-term inhalative	3000 mg/m3	Workers	Systemic
DNEL long-term inhalative	643 mg/m3	Consumers	Systemic
DNEL long-term dermal	432 mg/kg bw/day	Workers	Systemic
DNEL long-term dermal	214 mg/kg bw/day	Consumers	Systemic

8.2 - Exposure controls

Appropriate engineering controls

- No information available.

Individual protection measures, such as personal protective equipment

- Tested protective gloves must be worn



Silikon-Spray 400 ml

- The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances.

- Suitable material: NBR (Nitrile rubber)

- Eye protection: not required.

- Suitable respiratory protection apparatus: AX

SECTION 9: Physical and chemical properties

9.1 - Information on basic physical and chemical properties

Physical state	Liquid	Appearance	Aerosol
Colour	colourless	Odour	
Odour threshold		No data available	
pH		No data available	
Melting point		No data available	
Freezing point		No data available	
Boiling point		No data available	
Flash point		-60 °C	
Evaporation rate		No data available	
flammability		No data available	
Lower explosion limit		1 % Vol.	
Upper explosion limit		10.9 % Vol.	
Vapour pressure		2600 hPa	
Vapour density		No data available	
Relative density		No data available	
Density		0.62 g/cm ³	
Solubility (Water)		No data available	
Solubility (Ethanol)		No data available	
Solubility (Acetone)		No data available	
Solubility (Organic solvents)		No data available	
Log KOC		No data available	
Auto-ignition temperature		> 200 °C	
Decomposition temperature		No data available	
Kinematic viscosity		No data available	
Dynamic viscosity		No data available	

Particle characteristics

Particle size	No data available
---------------	-------------------

9.2 - Other information

VOC content	92.5 %
Minimum ignition energy	No data available

Silikon-Spray 400 ml

Conductivity	No data available
--------------	-------------------

SECTION 10: Stability and reactivity

10.1 - Reactivity

- This material is considered to be non-reactive under normal use conditions.

10.2 - Chemical stability

- The product is chemically stable under recommended conditions of storage, use and temperature.

10.3 - Possibility of hazardous reactions

- No hazardous reaction when handled and stored according to provisions.

10.4 - Conditions to avoid

- No information available.

10.5 - Incompatible materials

- No information available.

10.6 - Hazardous decomposition products

- Does not decompose when used for intended uses.

SECTION 11: Toxicological information

11.1 - Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity - Not classified

Toxicity : Mixture

LD50 oral (rat)	No data available
LD50 dermal (rat)	No data available
LD50 dermal (rabbit)	No data available
LC50 inhalation (rat)	No data available
LC50 inhalation dusts and mists (rat)	No data available
LC50 inhalation vapours (rat)	No data available

- Based on available data, the classification criteria are not met.

Toxicity : Substances

Hydrocarbons, C6, isoalkanes, <5% n-hexane ()	
LD50 oral (rat)	> 16750 mg/kg
LD50 dermal (rabbit)	> 3350 mg/kg
pentane isopentane, 2-methylbutane (109-66-0)	
LD50 oral (rat)	2000 mg/kg < V < 5000 mg/kg
LC50 inhalation (rat)	25.3 ppmV

Skin corrosion/irritation - Irritation, Category 2 - Causes skin irritation

- Irritating to skin.

Silikon-Spray 400 ml

<u>Serious eye damage/eye irritation</u>	- Not classified
<u>Respiratory or skin sensitisation</u>	- Not classified
<u>Germ cell mutagenicity</u>	- Not classified
<u>Carcinogenicity</u>	- Not classified
<u>Reproductive toxicity</u>	- Not classified
<u>STOT-single exposure</u>	- STOT-single exposure - Category 3 (H336) - May cause drowsiness or dizziness
<u>STOT-repeated exposure</u>	- Not classified
<u>Aspiration hazard</u>	- Aspiration hazard - Category 1 - May be fatal if swallowed and enters airways

11.2 - Information on other hazards

SECTION 12: Ecological information

12.1 - Toxicity

Toxicity : Mixture

EC50 48 hr crustacea	No data available
LC50 96 hr fish	No data available
ErC50 algae	No data available
ErC50 other aquatic plants	No data available
NOEC chronic fish	No data available
NOEC chronic crustacea	No data available
NOEC chronic algae	No data available
NOEC chronic other aquatic plants	No data available

Toxicity : Substances

Hydrocarbons, C6, isoalkanes, <5% n-hexane ()

LC50 96 hr fish	18.27 mg/l
ErC50 algae	13.56 mg/l

- Toxic to aquatic life with long lasting effects.

12.2 - Persistence and degradability

Biochemical oxygen demand (BOD)	No data available
Chemical oxygen demand (COD)	No data available
% of biodegradation in 28 days	No data available

- No information available.

12.3 - Bioaccumulative potential

Bioconcentration factor (BCF)	No data available
Log KOC	No data available

- No indication of bioaccumulation potential.

Silikon-Spray 400 ml

12.4 - Mobility in soil

- No information available.

12.5 - Results of PBT and vPvB assessment

12.6 - Endocrine disrupting properties

12.7 - Other adverse effects

- No information available.

SECTION 13: Disposal considerations

13.1 - Waste treatment methods

Waste treatment methods

- Dispose of waste according to applicable legislation.
- packaging containing residues of or contaminated by dangerous substances
- Metallic packaging

Sewage disposal

- No information available.

Special precautions for waste treatment

- No information available.

Community or national or regional provisions

- No information available.

SECTION 14: Transport information

14.1 - UN number or ID number

<u>UN number (ADR)</u>	:	UN1950
<u>UN number (RID)</u>	:	UN1950
<u>UN number (ADN)</u>	:	Not applicable
<u>UN number (IMDG)</u>	:	UN1950
<u>UN number (IATA)</u>	:	UN1950

14.2 - UN proper shipping name

<u>UN proper shipping name (ADR)</u>	:	AEROSOLS
<u>UN proper shipping name (RID)</u>	:	AEROSOLS
<u>UN proper shipping name (IMDG)</u>	:	AEROSOLS
<u>UN proper shipping name (IATA)</u>	:	AEROSOLS, FLAMMABLE

14.3 - Transport hazard class(es)

Silikon-Spray 400 ml

ADR Transport hazard class(es) : 2
ADR Classification code: : 5F
Pictograms



Transport hazard class(es) (RID) : 2
Pictograms



Transport hazard class(es) (IMDG) : 2
Pictograms



Transport hazard class(es) (IATA) : 2.1
Pictograms



14.4 - Packing group

Packing group :
Packing group (RID) :
Packing group (IMDG) :
Packing group (IATA) :

14.5 - Environmental hazards

Environmental hazards : Yes.
Marine pollutant : Hazardous to the aquatic environment - Aquatic Chronic 2

14.6 - Special precautions for user

Silikon-Spray 400 ml

ADR

<u>ADR Classification code:</u>	:	5F
<u>ADR Special provisions</u>	:	190+327+344+625
<u>ADR Limited quantity (LQ)</u>	:	1L
<u>ADR Excepted quantities</u>	:	E0
<u>ADR Packing instructions</u>	:	P207 LP200
<u>ADR Special packing provisions</u>	:	PP87 RR6 L2
<u>ADR Mixed packing provisions</u>	:	MP9
<u>Instructions for portable tanks and bulk containers</u>	:	
<u>Special provisions for portable tanks and bulk containers</u>	:	
<u>ADR tank code</u>	:	
<u>ADR tanks special provisions</u>	:	
<u>Vehicle for tank carriage</u>	:	
<u>ADR Transport category</u>	:	2
<u>ADR Tunnel restriction code</u>	:	D
<u>ADR Special provisions loading, unloading and handling</u>	:	CV9 CV12
<u>Special provisions - Packages</u>	:	V14
<u>Special provisions - Bulk</u>	:	
<u>Special provisions - Operation</u>	:	S2
<u>ADR Hazard identification number (Kemler No.)</u>	:	

RID

<u>Special provisions</u>	:
<u>Limited quantity (LQ)</u>	:
<u>Excepted quantities</u>	:

IMDG

<u>Special provisions</u>	:	63 190 277 327 344 381 959
<u>Limited quantity (LQ)</u>	:	
<u>Excepted quantities</u>	:	E0
<u>Packing instructions</u>	:	P207 LP200
<u>Special packing provisions</u>	:	PP87 L2
<u>IBC instruction(s)</u>	:	
<u>IBC provisions</u>	:	
<u>Instructions for portable tanks and bulk containers</u>	:	
<u>Special provisions for portable tanks and bulk containers</u>	:	
<u>EmS codes</u>	:	F-D, S-U
<u>Stowage and handling</u>	:	Category None SW1 SW22
<u>Segregation</u>	:	SG69
<u>Properties and observations</u>	:	

Silikon-Spray 400 ml

IATA

PCA - Excepted quantities	:	E0
PCA - Limited Quantity - Packing Instructions	:	Y203
PCA - Limited Quantity - Maximum Net Quantity per Package	:	30kg
PCA - Packing Instructions	:	203
PCA - Maximum Net Quantity per Package	:	75kg
CAO - Packing Instructions	:	203
CAO - Maximum Net Quantity per Package	:	150kg
Special Provisions	:	A145 A167 A802
ERG Code	:	10L

14.7 - Maritime transport in bulk according to IMO instruments

SECTION 15: Regulatory information

15.1 - Safety, health and environmental regulations/legislation specific for the substance or mixture

Substances REACH candidates None

Substances Annex XIV None

Substances Annex XVII None

VOC content 92.5 %

15.2 - Chemical Safety Assessment

Chemical safety assessment carried out for the product - No information available.

SECTION 16: Other information

SDS versions

Version	Issue date	Author	Description of the amendments
1	6/22/2022		

Texts of the regulatory sentences

Aerosol 1	Aerosol - Category 1
Aquatic Chronic 2	Hazardous to the aquatic environment - Aquatic Chronic 2
Asp. Tox. 1	Aspiration hazard - Category 1
Flam. Liq. 2	Flammable liquid and vapour. - Category 2
H222	Extremely flammable aerosol
H225	Highly flammable liquid and vapour
H229	Pressurised container: May burst if heated
H304	May be fatal if swallowed and enters airways
H315	Causes skin irritation
H336	May cause drowsiness or dizziness
H411	Toxic to aquatic life with long lasting effects
Skin Irrit. 2	Irritation, Category 2
STOT SE 3 (H336)	STOT-single exposure - Category 3 (H336)



Silikon-Spray 400 ml

*** **